

**Test Report No. 54S076035/A/LCM**  
**dated 22 Oct 2007**



**Note:** This report is issued subject to TÜV SÜD PSB's "Terms and Conditions Governing Technical Services". The terms and conditions governing the issue of this report are set out as attached within this report.

**SUBJECT:**

Laboratory measurement of airborne sound insulation of "GISS" autoclaved lightweight concrete (ALC) wall panel submitted by Godiniland on 19 Sep 2007.

**TESTED FOR:**

Godiniland  
Ground Floor, 2 Mill Street,  
Perth West Australia 6000

Attn: Mr David Teh

**DATE OF TEST:**

16 Oct 2007

**DESCRIPTION OF SAMPLE:**

A "GISS" autoclaved lightweight concrete (ALC) wall panel system of dimension of 3.19m (width) x 3.16m (height) x 100mm (thick) was installed onto the sample carrier by Tarlic Engineering Construction.

<u>Dimension</u>	<u>Quantity</u>
a) 3.19m (length) x 0.6m (width) x 100mm (thick)	5 pieces
b) 3.19m (length) x 0.19m (width) x 100mm (thick)	1 piece

The density of the ALC wall panel is said to be 750kg/m<sup>3</sup>.

ALC grout and sealant was used to seal the joint of the external side of the wall. Normal concrete was used to seal the joint of the internal side of the wall.



Laboratory:  
TÜV SÜD PSB Pte. Ltd.  
Testing Group  
No.1 Science Park Drive  
Singapore 118221

Phone : +65-6885 1333  
Fax : +65-6776 8670  
E-mail: testing@tuv-sud-psb.sg  
www.tuv-sud-psb.sg  
Co. Reg : 199002667R

Regional Head Office:  
TÜV SÜD Asia Pacific Pte. Ltd.  
3 Science Park Drive  
#04-01/05 The Franklin  
Singapore 118223



LA-2007-0380-A  
LA-2007-0380-A-1  
LA-2007-0381-F  
LA-2007-0382-B  
LA-2007-0383-G  
LA-2007-0384-G  
LA-2007-0385-E  
LA-2007-0386-C

The results reported herein have been performed in accordance with the laboratory's terms of accreditation under the Singapore Accreditation Council - Singapore Laboratory Accreditation Scheme. Tests/Calibrations marked "Not SAC-SINGLAS Accredited" in this Report are not included in the SAC-SINGLAS Accreditation Schedule for our laboratory.



**METHOD OF TEST:**

The test was conducted in accordance with ISO 140 – 3 : 1995 “Laboratory measurements of airborne sound insulation of building elements”.

Area of test specimen : 3.185m x 3.160m = 10.07m<sup>2</sup>

Air temperature in both source room and receiving room : 26°C

Relative air humidity in both source room and receiving room : 59%

Source room volume : 73m<sup>3</sup>

Receiving room volume : 86m<sup>3</sup>

Location of the test : Acoustics Lab of TÜV SÜD PSB Pte Ltd

**TEST EQUIPMENT:**

The following instruments were used for the test.

- 1) A dual-channel real-time frequency analyser (B&K Type 2133)
- 2) An Omni-loudspeaker (B&K Type 4296)
- 3) Two sets of ½” condenser microphones (B&K Type 4190)
- 4) Two sets of microphone preamplifiers (B&K Type 2669)
- 5) A sound pressure level calibrator (Norsonic Type 1251)
- 6) A sound source amplifier (Crown model CE 1000)
- 7) Two sets of rotating microphone booms (B&K Type 3923)



**TEST PROCEDURES:**

- 1) Instrumentation was set up according to ISO 140 - 3.
- 2) Measurement system was calibrated using a sound level calibrator Norsonic Type 1251.
- 3) Background noise level for both source room and receiving room were measured.
- 4) Sound source system was switched on and maintained at constant level. The sound pressure level in the receiving room was ensured to be 15dB higher than the background noise level.
- 5) Recording time for both rotating microphone booms was set to 64s which equals to the time taken by the booms to complete two revolutions.
- 6) Sound pressure level difference between the source room and the receiving room was measured with a dual – channel acoustic analyser (B&K 2133), and the measurement was repeated 3 times.
- 7) Step 6 was repeated after the loudspeaker was moved to new position.
- 8) Reverberation time (RT) of the receiving room was measured from two different loudspeaker positions. Each loudspeaker position was measured 2 times.
- 9) The mean values of the six readings for sound pressure level difference and four readings for RT values were calculated.
- 10) Values of sound reduction index were determined for each 1/3 octave frequency band from 100Hz to 5kHz based on the mean values of step 9.
- 11) Weighted sound reduction index ( $R_w$ ) (single number for rating sound insulation of the sample) and its adaptation terms ( $C$ ,  $C_{tr}$ ) according to ISO 717-1 was determined at the frequency of 500Hz of the shifted reference curve (see figure 1).

A handwritten signature in black ink, consisting of several stylized, overlapping loops and lines.

**RESULTS:**

Values of sound reduction index (R) of the tested sample were tabulated in Table 1. Sound Insulation Rating is computed according to ISO 717 - 1 : 1996 "Acoustics - Rating of sound insulation in buildings and of building elements – Part 1: Airborne sound insulation".

**Table 1 : Measured values of the test sample and values of the shifted reference curve for  $R_w = 38$**

1/3 Octave Band Frequency (Hz)	Measured Sound Reduction Index, R (dB)	Shifted Reference Curve $R_w = 38$ (dB)	Deficiency
100	32.1	19.0	0.0
125	34.7	22.0	0.0
160	33.4	25.0	0.0
200	30.8	28.0	0.0
250	29.6	31.0	1.4
315	29.7	34.0	4.3
400	30.0	37.0	7.0
500	30.8	<b>38.0</b>	7.2
630	33.6	39.0	5.4
800	37.8	40.0	2.2
1000	40.9	41.0	0.1
1250	43.1	42.0	0.0
1600	45.9	42.0	0.0
2000	47.8	42.0	0.0
2500	49.9	42.0	0.0
3150	51.9	42.0	0.0
4000	53.9	42.0	0.0
5000	56.1	42.0	0.0
<b>Total deficiency (125Hz – 4000Hz) :</b>			<b>28</b>

The values in Table 1 were plotted as shown in Figure 1.


**Remark:** The tested sample has a weighted sound reduction index,  $R_w(C, C_{tr}) = 38 (-1, -3)$ .

  
Lem Chee Meng  
Testing Officer

  
Dr Sun Qiqing  
Assistant Vice President  
Acoustics & Packaging  
Testing Group

**RESULTS: (cont'd)**

**Figure 1 : Sound insulation performance of "GISS" autoclaved lightweight concrete wall panel**



—◆— Measured sound reduction index, R

— Shifted reference curve,  $R_w = 38$





Figure 2 : Test setup in Source Room



Figure 3 : Test setup in Receiving Room






Figure 4 : Joint Detail and Cross Section of ALC wall panel



**Test Report No. 54S076035/A/LCM**  
**dated 22 Oct 2007**



This Report is issued under the following conditions:

1. Results of the testing/calibration in the form of a report will be issued immediately after the service has been completed or terminated.
2. Unless otherwise requested, a report shall contain only technical results. Analysis and interpretation of the results and professional opinion and recommendations expressed thereupon, if required, shall be clearly indicated and additional fee paid for, by the Client.
3. This report applies to the sample of the specific product/equipment given at the time of its testing/calibration. The results are not used to indicate or imply that they are applicable to other similar items. In addition, such results must not be used to indicate or imply that TÜV SÜD PSB approves, recommends or endorses the manufacturer, supplier or user of such product/equipment, or that TÜV SÜD PSB in any way "guarantees" the later performance of the product/equipment.
4. The sample/s mentioned in this report is/are submitted/supplied/manufactured by the Client. TÜV SÜD PSB therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.
5. Additional copies of the report are available to the Client at an additional fee. No third party can obtain a copy of this report through TÜV SÜD PSB, unless the Client has authorised TÜV SÜD PSB in writing to do so.
6. TÜV SÜD PSB may at its sole discretion add to or amend the conditions of the report at the time of issue of the report and such report and such additions or amendments shall be binding on the Client.
7. All copyright in the report shall remain with TÜV SÜD PSB and the Client shall, upon payment of TÜV SÜD PSB's fees for the carrying out of the tests/calibrations, be granted a license to use or publish the report to the third parties subject to the terms and conditions herein, provided always that TÜV SÜD PSB may at its absolute discretion be entitled to impose such conditions on the license as it sees fit.
8. Nothing in this report shall be interpreted to mean that TÜV SÜD PSB has verified or ascertained any endorsement or marks from any other testing authority or bodies that may be found on that sample.
9. This report shall not be reproduced wholly or in parts and no reference shall be made by the Client to TÜV SÜD PSB or to the report or results furnished by TÜV SÜD PSB in any advertisements or sales promotion.
10. Unless otherwise stated, the tests are carried out in TÜV SÜD PSB Pte Ltd, No.1 Science Park Drive Singapore 118221.

May 2007